

ALGE-TIMING

Startbeep STB1



Version- E23-11-02

Manual

Important Information

General

Before using your **ALGE-TIMING** device read the complete manual carefully. It is part of the device and contains important information about installation, safety and its intended use. This manual cannot cover all conceivable applications. For further information or in case of problems that are mentioned not at all or not sufficiently detailed, please contact your **ALGE-TIMING** representative. You can find contact details on our homepage www.alge-timing.com

Safety

Apart from the information of this manual all general safety and accident prevention regulations of the legislator must be taken into account.

The device must only be used by trained persons. The setting-up and installation must only be executed according to the manufacturer's data.

Intended Use

The device must only be used for its intended applications. Technical modifications and any misuse are prohibited because of the risks involved! **ALGE-TIMING** is not liable for damages that are caused by improper use or incorrect operation.

Power supply

The stated voltage on the type plate must correspond to voltage of the power source. Check all connections and plugs before usage. Damaged connection wires must be replaced immediately by an authorized electrician. The device must only be connected to an electric supply that has been installed by an electrician according to IEC 60364-1. Never touch the mains plug with wet hands! Never touch live parts!

Cleaning

Please clean the outside of the device only with a smooth cloth. Detergents can cause damage. Never submerge in water, never open or clean with wet cloth. The cleaning must not be carried out by hose or high-pressure (risk of short circuits or other damage).

Liability Limitations

All technical information, data and information for installation and operation correspond to the latest status at time of printing and are made in all conscience considering our past experience and knowledge. Information, pictures and description do not entitle to base any claims. The manufacturer is not liable for damage due to failure to observe the manual, improper use, incorrect repairs, technical modifications, use of unauthorized spare parts. Translations are made in all conscience. We assume no liability for translation mistakes, even if the translation is carried out by us or on our behalf.

Disposal

If a label is placed on the device showing a crossed out dustbin on wheels (see drawing), the European directive 2002/96/EG applies for this device.

Please get informed about the applicable regulations for separate collection of electrical and electronical waste in your country and do not dispose of the old devices as household waste. Correct disposal of old equipment protects the environment and humans against negative consequences!



Copyright by **ALGE-TIMING GmbH**

All rights reserved. Any duplication, either in full or in part, requires the prior written consent of the copyright holder.

Table of Content

1	STARTBEEP STB1 COMPONENTS.....	4
2	General	4
3	SWITCH POSITIONS (1)	5
4	GENERAL FUNCTIONS	5
4.1	PRE-WARNING	5
4.2	SWITCH COUNTDOWN INTERVALS (2)	5
4.3	START OUTPUT TO START A TIMING DEVICE	5
4.4	SYNCHRONIZATION AND EXTERNAL HANDSWITCH.....	5
5	PROGRAMS	6
5.1	PROGRAMS 1 – 9 (SWITCH POSITION 1- 9)	6
5.2	USER PROGRAMMABLE INTERVAL.....	6
5.3	MANUAL COUNT-DOWN for SPEED-CLIMBING (>07-2017).....	6
5.4	MANUAL COUNT-DOWN for PARALLEL SLALOM(>11-2020).....	6
5.5	MANUAL COUNTDOWN THROUGH PRESSING A BUTTON.....	7
5.6	HORN	7
6	TECHNICAL DATA	8
6.1	CONNECTION SYSTEM	8
6.1.1	INPUTS.....	8
6.1.2	OUTPUTS.....	8

Subject to changes

Copyright by:

ALGE-TIMING GmbH
Rotkreuzstrasse 39
A-6890 Lustenau
Austria

office@alge-timing.com
www.alge-timing.com

1 STARTBEEP STB1 COMPONENTS



- 1..... internal switch: e.g. for manual start or horn
- 2..... rotary switch: switch with position off (0) and 15 function positions
- 3..... green and black banana jacks: for synchronization and external hand switch
- 4..... white banana jacks: potential free contact to start a timer
- 5..... 6 pin DIN jack: connection for net charger ALGE NGL13 or external switch
- 6..... screwed hook to fix the Startbeep chain to a post

2 General

The ALGE Startbeep is a device for regulated and organized starts

The Startbeep has 9 fixed and 2 selectable programs. It has also a program which starts a countdown by pressing the red button (2).

All countdown programs can be started with or without a pre-warning. The pre-warning is an acoustic signal, starting ten seconds before the start.

3 SWITCH POSITIONS (1)

0.....	Power off
1.....	Countdown every 10 seconds (Pre-warning not possible)
2.....	Countdown every 15 seconds
3.....	Countdown every 20 seconds
4.....	Countdown every 30 seconds
5.....	Countdown every 40 seconds
6.....	Countdown every 45 seconds
7.....	Countdown every 60 seconds
8.....	Countdown every 1 minute 30 seconds
9.....	Countdown every 2 minute 30 seconds
A.....	User programmable time A
B.....	till July 2017, User programmable time B
B.....	from July 2017, Manual 3 Seconds Countdown Speed-Climbing
B+button	from Nov. 2020: Manual 3 Seconds Countdown SSD1 Parallel Ski
C.....	Set minutes
D.....	Set seconds
E.....	Horn (Acoustic signal)
F.....	Manual (countdown by pressing button (1))



4 GENERAL FUNCTIONS

4.1 PRE-WARNING

The standard countdown is without a pre-warning (no ten second tone before the start)
 If you would like to work with a pre-warning, press and hold the red button (2) while turning the device on. Now every countdown program has a pre-warning tone ten seconds before the start.

The pre-warning tone works only for intervals over 10 seconds in duration.

4.2 SWITCH COUNTDOWN INTERVALS (2)

You can switch the countdown intervals at any time to a new position. Once you reach the new position, press the red button (2) to confirm the new countdown interval.

4.3 START OUTPUT TO START A TIMING DEVICE

If you connect the two white banana jacks (4) on the Startbeep to another timing device (Start input), you can start the timer with the Startbeep. The timer starts with the beginning of the last beep (high tone) of the countdown.

4.4 SYNCHRONIZATION AND EXTERNAL HANDSWITCH

The Startbeep can be synchronized with other timing devices through the green and black banana jacks (3). This makes it possible to control the lead and lag times.

It is also possible to plug a hand switch into the green and black banana jacks (3) to start the manual countdown or horn.

5 PROGRAMS

5.1 PROGRAMS 1 – 9 (SWITCH POSITION 1- 9)

A fixed interval is programmed for each switch position between 1 and 9. If you press the red button (2) while you switch the device on the pre-warning tone is set. After you turn the switch to the position you need, you need to press the red button (2) to start the countdown.

5.2 USER PROGRAMMABLE INTERVAL

One countdown time can be programmed individually. You can use a start interval between 6 seconds and 99:59 minutes.

TO SET USER PROGRAMMABLE INTERVALS

- Rotate the switch (1) to position "C"
- Every time you press the red button (2) it increments by a minute
- Rotate the switch (1) to position "D"
- Every time you press the red button (2) it increments by a second
- Rotate switch (1) to position "A" and store the interval by pressing the red button (2)
- The user programmable interval is stored until you turn the Startbeep off

5.3 MANUAL COUNT-DOWN for SPEED-CLIMBING (>07-2017)

If you turn the switch (1) to position "B", the manual 3-second countdown is for speed climbing is activated. A 3 second countdown starts every time the red button (2) is pressed or an impulse is sent to the green-black banana socket (3). This countdown corresponds to the regulations for speed climbing.

Triggering the Countdown	3 Seconds before Start	no sound
	2 Seconds before Start	deep sound
	1 Second before Start	deep sound
	Start	high sound

This function is only integrated in STB1s that were purchased after July 2017 or whose EPROM was replaced after this date.

If you like to upgrade your STB1 with this new function please contact your ALGE sales representative!

5.4 MANUAL COUNT-DOWN for PARALLEL SLALOM(>11-2020)

If the red button (2) is pressed while the switch (1) is turned to position "B", the manual 3-second countdown is activated for parallel slalom. A 3 second countdown starts every time the red button (2) is pressed or an impulse is sent to the green-black banana socket.

Triggering the Countdown	3 Seconds before Start	deep sound
	2 Seconds before Start	deep sound
	1 Second before Start	deep sound
	Start	high sound

This function is only integrated in STB1s that were purchased after November 2020 or whose EPROM was replaced after this date.

If you like to upgrade your STB1 with this new function please contact your ALGE sales representative!

5.5 *MANUAL COUNTDOWN THROUGH PRESSING A BUTTON*

If you turn the switch (1) to position “F”, you can start the countdown by pressing the red button (2).

5.6 *HORN*

Rotate the switch (1) to position “E”. The tone sounds as long as you press the red button (2).

6 TECHNICAL DATA

Quartz frequency: 4,608 MHz

Temperature range: -25 to +45 degrees Celsius

Storage temperature: -40 to +65 degrees Celsius

Power supply: 1 alkaline battery 9V or
1 NiCd rechargeable battery 9V (8.4 or 7.2V)

Power consumption: 2 mA without speaker output
150 mA during speaker output

Recharge time (if using NiCd battery):
14 hours (do not charge the battery longer than 16 hours, it may decrease the life of the battery).

Working time with full NiCd charge:

.	With 30 sec. Countdown and without pre-warning:	20 hours
.	With 30 sec. Countdown and with pre-warning:	10 hours

Working time with full alkaline battery:

.	With 30 sec. Countdown and without pre-warning:	80 hours
.	With 30 sec. Countdown and with pre-warning:	40 hours


Operating elements: 1 turn switch
1 button

6.1 CONNECTION SYSTEM

6.1.1 INPUTS

- **6 pin DIN jack (5)**
Connection for net charger (NGL13) and external hand switch with DIN plug

1.....	External button
2.....	No Connection
3.....	Ground
4.....	External supply (+10 to +15V)
5.....	No connection
6.....	No connection



- **Green & Black banana jacks (3)**
Green jack: external button (like pin 1)
Black jack: ground

6.1.2 OUTPUTS

- **Two white Banana jacks (4):**
Normally open relays to start another timer
(Reed relay max. 12V/0.5A)
- **Green and black banana jack (3)**
input for synchronized start and input for hand switch (e.g. manual start)